

The excellent appearance in accord with ergonomic design

Integrated body design makes products maintains long-term stability.

High quality 3W LED lamp and long usage life.

Head: Binocular Head, Inclined at 30°, 360° Rotatable, Interpupillary Distance 54-75 mm, Diopter Adjustable

± 5 On Left Tube

Eyepiece: Wide Field Eyepiece WF 10X/1 8mm

Objective: Plan Achromatic Objectives 4x, 10x, 40xs, 100xs(oil) Viewing Head: Articulated Free Trinocular Head, 30°inclined,

Interpupillary Distance 54-75mm

Nosepiece: Reverse Quadruple Nosepiece (inward facing) Focusing System: Coaxial Coarse and Fine Adjustments, Fine Division 0.002mm, Coarse Stroke 36mm Supplied With An Adjustable Rack Stop To Prevent Damage To Sample And Objectives, The Coarse Adjustment Are Equipped With Friction

Control

Stage: Double Layer Mechanical Stage 110x125mm,

Moving Range 30x75mm

Illumination: 3W LED, Brightness

Adjustable, Powered by 110-240V Adapter

Inbuilt Battery Backup Facility

Packaging: Inner Thermocol/Styrofoam Packing and Outer Cardboard Box.

RESEARCH BINOCULAR MICROSCOPE **AXL-Bino**

















